

Klick&Show K-WM

Technical specification

Part number	7488 000 350
Wireless mirroring of screen content (BYOD)	yes
Wireless transmission of USB camera/audio (BYOM)	-
Compatible transmitters	-
Windows 10 / 11	Klick&Show app / Googlecast / Miracast (optional)
macOS	Klick&Show app, AirPlay, Googlecast
Mobile devices	Android app / AirPlay / Googlecast / Miracast (optional)
Miracast support	optional, supports Miracast-Direct (P2P) and Miracast-over-Infrastructure (MS MICE)
Maximum resolution, wireless	1080p: with Klick&Show app / Airplay / Miracast / Googlecast
Simultaneous connections RJ45	> 30
Simultaneous connections via internal WLAN	≤ 16
Splitscreen	up to 4 simultaneously, layout adjustable
Low latency mouse cursor	yes, Klick&Show app for Windows / macOS
Touch-Back /USB-HID support	yes, e.g. for use with interactive displays (touchscreens), whiteboards or projectors
WiFi frequency band	2.4 / 5 GHz
WiFi standard	WiFi 5 (IEEE 802.11b/g/n/ac)
WiFi antennas	2x2 MIMO
WiFi bandwidth	up to 1200 Mbps
Security standard	WiFi: WPA PSK, WPA2 PSK - Video transmission encrypted with AES-256 bit + RSA1024 bit
HDMI output	1x HDMI 2.0 / 3840x2160@60/30 Hz, 1920x1080@60Hz, 1280x720@60Hz
HDCP version	HDCP 1.4, HDCP 2.0
Audio input	Klick&Show app / AirPlay / Googlecast / Miracast (with optional Miracast USB WiFi adapter)
Audio output (analog)	1x 3.5 mm stereo jack
USB 2.0 (type C)	1x (front)
USB 2.0 (type A)	1x (front)
USB 3.0 (type A)	1x (rear)
LAN (RJ45)	1x 1000 Mbps with PoE, 1x 100 Mbps
PoE standard	IEEE802.3af
Control	Network: Web GUI, Telnet; RS232: 1x 3-pin Euroblock (rear)
Housing / color	Aluminium, plastic / similar to Space Grey, black
Dimensions (W x D x H)	165 x 95 x 25 mm (incl. antennas 165 x 215 x 25 mm)
Weight	0.38 kg
Power supply unit	plug-in power supply with interchangeable plugs (Euro AV, UK, US), 12 V / 1.5 A
Power consumption	max. 18 W

Kindermann GmbH

Mainparkring 3 | D-97246 Eibelstadt | Germany

Email: info@kindermann.de

Subject to alterations | 7488000350 | 08.2024

www.kindermann.com