

Klick&Show Transmitters Technical specification

Transmitter type	4K HDMI transmitter	4K USB-C transmitter	HDMI transmitter	USB-C transmitter
Part number	7488 000 364	7488 000 365	7488 000 344	7488 000 345
Connector	HDMI, USB-A	USB-C	HDMI, USB-A	USB-C
Compatible base unit	Klick&Show K-40/K-42, K-FX & K-FX Plus			
Integrated CD-ROM memory for apps and drivers	Yes, when paired with K-FX series base unit. No CD-ROM memory when paired with K-40 series base unit.			
USB standard	2.0			
Input resolutions	up to 3840x2160p@30Hz		up to 2540x1440p@60Hz	
Video standard	HDMI 1.4, HDCP 1.4	DP 1.2, eDP 1.4, HDCP 1.3	HDMI 1.4, HDCP 1.4	DP 1.2, eDP 1.4, HDCP 1.3
Audio	2CH PCM			
USB HID function	yes			
Frame rate	60 fps (max.)			
Output resolution	3840x2160p (max.)		1080p (max.)	
Latency	< 80 ms		< 100 ms	
WiFi frequency band	2.4 / 5 GHz			
WiFi standard	WiFi 6 (IEEE 802.11b/g/n/ac/ax)		WiFi 5 (IEEE 802.11b/g/n/ac)	
WiFi antennas	MIMO 2x2			
WiFi bandwidth	up to 866 Mbps			
WiFi range	typical: 35 m with unobstructed line-of-sight between transmitter and base unit			
WiFi security standard	WPA PSK, WPA2 PSK, WPA3 PSK		WPA PSK, WPA2 PSK	
Housing / color	plastic / black			
Operation	1x tactile main button, 2x tactile auxiliary button		sensor button with vibration feedback	
Auxiliary buttons, function assignment	2x, customizable for K-FX Plus, fixed for K-FX/K-40		none	
LED	multi-color LED status display		dual-color LED status display (green / red)	
Dimensions (W x D x H)	77 x 77 x 18 mm		80 x 60 x 15 mm	
Connection cable (length)	approx. HDMI 11 cm, approx. USB 20 cm	approx. 11 cm	approx. HDMI 11 cm, approx. USB 20 cm	approx. 11 cm
Weight	approx. 100 g	approx. 90 g	approx. 100 g	approx. 90 g
Power consumption	approx. 2.5 W			
Power supply	via USB 5V			

Kindermann GmbH

Mainparkring 3 | D-97246 Eibelstadt | Germany

Email: info@kindermann.de

Subject to alterations | 7488000344 / 7488000345 / 7488000364 / 7488000365 | 08.2024

www.kindermann.com